

SGVW2

2.4 mil White Gloss Vinyl Vehicle Wrap Film



A Premium 2.4 Mil Seven Year Digital Gloss Vehicle Vinyl Media With An Acrylic Adhesive And An Easy Application Air Release Liner

- Specifically engineered and warranty guaranteed for most vehicle wrap and decal applications based printers
- The 90# air-egress liner allows for good lay-flat and air free application
- Designed to be applied to corrugations, riveted surfaces and flat to moderate curves
- The construction can be used on vans, trucks, sedans of all sizes and fleet and recreational vehicles
- Excellent color brilliance and image definition
- Grey permanent adhesive offers excellent opacity and exceptional repositionable qualities
- Good dimensional stability
- SGVW2 warranty information and application guide located in the Read&Co. document download center
- Use with Read&Co. PSGVW2 / PSMVW2 Laminates for 7 Year Warranty

Lamination & Mounting

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

Roll Configurations

FINISHED ROLLS	CORE	PRINT SIDE
54"x150'	3"	PSO
60"x150'	3"	PSO

* CALL FOR ADDITIONAL SIZES

ORDER TODAY: readinkjet.com

Physical Specifications

ADHESIVE: Low Tack Acrylic
 CALIBER (mil): Vinyl: 2.4 (Calendared) / Adhesive: 0.8 To 1.1 / Liner: 7.0
 FINISH: Gloss
 LINER WEIGHT: 90#
 MATERIAL: Calendared PVC
 OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) / 30-70% R

FOR MORE INFORMATION: 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 || readinkjet.com