



Vescom Pearl Linen has a linen texture that resembles a decorative cloth-like surface. The pearlescent satin sheen finish provides an elegant backdrop for high-quality, high-resolution image reproduction on wide-format inkjet printers. This commercial grade wall covering is commonly used for murals found in corporate environments, healthcare facilities, entertainment venues and retail spaces. This low-VOC-emitting vinyl is Class A fire rating, making it an environmentally conscious choice.

Benefits	Applications	Customers
<ul style="list-style-type: none"><li>• Type II PVC</li><li>• Class A Fire Rating</li><li>• Meets EPA requirements for low VOC emitting products</li><li>• Meets or exceeds all Federal Requirements of CCC-W-408D for Type II wallcoverings</li></ul>	<ul style="list-style-type: none"><li>• Hotels</li><li>• Restaurants</li><li>• Corporate environment murals</li><li>• Retail</li><li>• Entertainment venues</li></ul>	<ul style="list-style-type: none"><li>• Large-format print service</li><li>• Design firm/ad agency</li><li>• In-house</li><li>• Sign companies</li></ul>



SPECIFICATIONS	
Material Type	100% PVC Face
Texture	Linen
Backing	Non-Woven Backing
Gauge	16 mil
Weight	20 oz/linear yd or 13 oz/yd <sup>2</sup>
Opacity	100%
Core Size	3in ID
Finish	Liquid top coatings can be used for added protection or desired finishes. To achieve Type II results, product must be paired with Marabu ClearShield Wall Armor.
RIP & Printer Media Settings	Optimal printer settings will vary from printer manufacturers. For the best and most consistent results a profile should be created using an external color calibrator in conjunction with your RIP and color matching software.
Light Fastness	The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.
Optimal Service Environment	For printing: 60°-80° F, 50% Relative Humidity. For end use: -40°-176° F (-40°-80° C).
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging.
Ink Compatibility	Compatible with all latex low-solvent, solvent, and UV-curable inks and printers.
Clean & Care	Easily cleaned using clear, warm water and mild soap with a natural sponge. For more difficult stains, the use of a stronger detergent may be tried. We recommend all cleaners first be tested to ensure compatibility with the wallcovering.
Shelf Life	1 year storage in original package under recommended storage conditions above.

SKU	Size	UPC Code	Region
PERLN54150	54 in x 150 ft	848412025170	AMS
PERLN54300	54 in x 300 ft	848412025132	AMS

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.