

PSMVW2

2.4 mil Matte Vehicle Overlamine Film



A Premium 2.4 Mil Matte PVC Film With An Optically Clear Permanent Acrylic Adhesive

- Specifically engineered and warranty guaranteed for most vehicle wrap and decal applications
- Offers protection from ultra violet radiation, moisture and other environmental exposures
- Five year resistance can be expected under normal exposure conditions
- Good dimensional stability
- Designed to be applied to corrugations, riveted surfaces and flat and moderate curves
- Warranty information and vehicle wrap application guide located in the Read&Co. document download center
- 7 year warranty solution when used in combination with SGVW2

Finishing Recommendations

Surfaces: Read&Co. laminates are specifically design to work with Read&Co. inkjet media. Read&Co. recommends that you use Read&Co. inkjet media to get the best results. All testing has been done with our branded media.

Surface Protection: Ensure that your graphic is completely dry prior to laminating. If inks are not dry before lamination the adhesion of the laminate can be adversely affected; outgassing of inks may occur, causing silvering to form under the laminate.

Laminating: If too much tension is applied during lamination, the product may curl toward the laminated side, and the edges may lift from the release liner and/or the application surface. Always double-check your machine settings.

Care And Maintenance

Packaging: If the output is being sent without mounting to a substrate such as FoamCore, always roll laminated prints with the graphic facing outward. It is not recommended to ship in a tube smaller than 6" in diameter.

Field Care & Maintenance: If graphics should become dirty while out in the field; we suggest using a damp cloth to remove dust and dirt. Do Not use Windex® or other cleaner; these products contain silicon and will damage the graphic. If a damp cloth doesn't do the job, use a solution up to 20% isopropyl alcohol (one part isopropyl alcohol to four parts water), and gently wipe clean. Markings can be removed by gently using a rubber eraser.

Material Handling: Unused laminate material should be placed back in its original packaging and stored at 70°F (21°C) for no more than 1 year; to obtain maximum adhesion.

Roll Configurations

FINISHED ROLLS	CORE	LINER SIDE
54"X150'	3"	In
60"X150'	3"	In

* CALL FOR ADDITIONAL SIZES

ORDER TODAY: readinkjet.com

Physical Specifications

FILM (mil): 2.4
 ADHESIVE (mil): 0.8 to 1.1
 LINER (mil): 1.1
 LINER WEIGHT: 90#
 SURFACE FINISH: Matte

FOR MORE INFORMATION: 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | readinkjet.com