

PSTAM

Antimicrobial Pressure Sensitive Textured Matte Laminate Film



Textured Polyolefin Film With Scuff Resistance

- Recommended for counter and floor graphics
- PVC free, Environmentally friendly
- Film with silver ions in a zeolite carrier added to inhibit reproduction of microorganisms
- Non-volatile controlled mechanism using silver zeolite
- Excellent slip resistance
- Lamination extends the life of your print
- FDA compliance for direct food contact

Finishing Recommendations

Surfaces: Read&Co. laminates are specifically design to work with Read&Co. inkjet media. Read&Co. recommends that you use Read&Co. inkjet media to get the best results. All testing has been done with our branded media.

Surface Protection: Ensure that your graphic is completely dry prior to laminating. If inks are not dry before lamination the adhesion of the laminate can be adversely affected; outgassing of inks may occur, causing silvering to form under the laminate.

Laminating: If too much tension is applied during lamination, the product may curl toward the laminated side, and the edges may lift from the release liner and/or the application surface. Always double-check your machine settings.

Care And Maintenance

Packaging: If the output is being sent without mounting to a substrate such as FoamCore, always roll laminated prints with the graphic facing outward. It is not recommended to ship in a tube smaller than 6" in diameter.

Field Care & Maintenance: If graphics should become dirty while out in the field; we suggest using a damp cloth to remove dust and dirt. Do Not use Windex® or other cleaner; these products contain silicon and will damage the graphic. If a damp cloth doesn't do the job, use a solution up to 20% isopropyl alcohol (one part isopropyl alcohol to four parts water), and gently wipe clean. Markings can be removed by gently using a rubber eraser.

Material Handling: Unused laminate material should be placed back in its original packaging and stored at 70°F (21°C) for no more than 1 year; to obtain maximum adhesion.

Roll Configurations

| FINISHED ROLLS | CORE | LINER SIDE |
|----------------|------|------------|
| 54"X150' | 3" | In |

* CALL FOR ADDITIONAL SIZES

ORDER TODAY:
readinkjet.com

Physical Specifications

CALIPER (mil): 3.75

LINER (mil): 1.2

FACE MATERIAL: 3.75

ADHESIVE TYPE: Permanent Solvent

MINIMUM APPLICATION TEMP: 50° F (10° C)

LINER TYPE: Clear Film

FOR MORE INFORMATION: 727 Venice Boulevard, Los Angeles, CA 90015

800.564.7323 | | readinkjet.com