## SBL8

### 8 mil Gloss PET Backlit Film



#### A Premium Gloss Solvent Backlit Film

- Great for backlit displays
- Excellent color brilliance and image resolution
- Recommended for both indoor and outdoor applications
- Good scratch resistance and waterproof with advanced coating
- · Can be hot or cold laminated
- Ideal solution for Duratrans
- Good rigidity and flatness for easy installation

#### **Lamination & Mounting**

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

#### Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

#### **Roll Configurations**

FINISHED ROLLS	CORE	PRINT SIDE
54"x100'	3"	PSO
60"X100'	3"	PSO

<sup>\*</sup> CALL FOR ADDITIONAL SIZES

# ORDER TODAY:

readinkjet.com

### **Physical Specifications**

CALIPER (mil): 8.2 MATERIAL: PET

BASIS WEIGHT (grams/m²): 285 SURFACE FINISH: High Gloss

OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) /

30-70% RH