# **SMABV4**

## 4 mil Matte High Tack Adhesive



#### **An Aggressive Adhesive Vinyl**

- Excellent color brilliance and image definition
- Good for indoor and outdoor applications
- 140 gsm release liner for optimum print results
- Solvent acrylic adhesive for superior bond

### **Lamination & Mounting**

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

#### Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

### **Roll Configurations**

FINISHED ROLLS	CORE	PRINT SIDE
54"x150'	3"	PSO
63"X150'	3"	PSO

<sup>\*</sup> CALL FOR ADDITIONAL SIZES

#### **ORDER TODAY:**

readinkjet.com

#### **Physical Specifications**

ADHESIVE: Permanent Acrylic

CALIPER (mil): 4.0 MATERIAL: PVC FINISH: Matte

LINER WEIGHT: 140 gsm

OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) /

30-70% RH WHITENESS: 93

LINER TYPE: Double sided PE coated silicone paper