# SSC8W

### 8 mil White Static Cling



### **A Premium White Cling Vinyl For Window Graphics**

- Cling allows for repositionable properties
- Does not leave any adhesive residues
- Ideal for window graphics

#### **Lamination & Mounting**

This product has been tested and approved for use with Read&Co. laminates and adhesives. Read Inkjet laminates provide durable protection from abrasion, moisture, Ultraviolet light and various types of damaging effects on indoor and outdoor applications. Recommendations for cold/pressure sensitive lamination and adhesives are SPEED: 3-5 feet per min and PRESSURE: 20-40psi (recommendations vary depending on the laminator, model and other variables). Read Lamination and Adhesives provide quick and efficient quality results without the need for heat.

#### Solvent, Eco-solvent, UV Curable And Latex Compatibility

This product is universally compatible with solvent, eco-solvent, UV curable and latex wide format digital inkjet printers. Read&Co inkjet materials provide an expanded color gamut and higher ink saturation for richer, more brilliant colors. Individual results may vary. Test thoroughly for your specific application.

#### **Roll Configurations**

FINISHED ROLLS	CORE	PRINT SIDE
54"x75'	3"	PSO
60"x150'	3"	PSO

<sup>\*</sup> CALL FOR ADDITIONAL SIZES

## ORDER TODAY:

readinkjet.com

#### **Physical Specifications**

CALIPER (mil): 7.5 LINER WEIGHT: 90#

MATERIAL: Calendered PVC

OPTIMAL PRINTING ENVIRONMENT: 70° F (21° C) /

30-70% RH