



With the look and feel of fine linen embossing, Vescom Tabby delivers colorful, high-definition wall art with high-end results. Certified for HP Latex Inks, this commercial grade media also meets Environmental Protection Agency (EPA) requirements for low-VOC emitting products and is Class A fire resistant.

A Type II Compliant, commercial grade wallcovering, Vescom Tabby is durable enough for commercial environments subject to wear and tear, while at the same time is environmentally safe for sensitive spaces like schools, hospitals and public buildings. Compatible with Latex, Eco-solvent, Solvent and UV inks, this phthalate- and formaldehyde-free substrate installs easily with common adhesives and installation techniques.

| Benefits  | Applications  | Customers  |
|---|---|--|
| <ul style="list-style-type: none"> <li>• Type II PVC</li> <li>• Commercial Grade, Class A Fire Rating</li> <li>• Meets EPA requirements for low VOC emitting products</li> <li>• Phthalate free substrate</li> <li>• Compatible with all Latex, Eco-Solvent, Solvent, and UV Inks</li> <li>• Certified for HP Latex Inks</li> </ul> | <ul style="list-style-type: none"> <li>• Corporate environment murals</li> <li>• Healthcare facilities</li> <li>• Schools</li> <li>• Retail and entertainment venues</li> </ul> | <ul style="list-style-type: none"> <li>• Large-format print service</li> <li>• Design firm/ad agency</li> <li>• In-house</li> <li>• Federal government</li> <li>• Schools</li> <li>• Sign companies</li> </ul> |



| SPECIFICATIONS               |  |
|------------------------------|--|
| Material Type                | 100% PVC Face  |
| Texture                      | Soft Linen   |
| Backing                      | Non Woven  |
| Gauge                        | 18 mil   |
| GSM                          | 448  |
| Weight                       | 20 oz linear yard  |
| Opacity                      | 100%   |
| Brightness                   | 87.10  |
| Whiteness                    | 89.44  |
| Finish                       | Liquid top coatings can be used for added protection or desired finishes. To achieve Type II results, product must be paired with Marabu ClearShield Wall Armor.   |
| Gloss Level                  | 6.4 (60)   |
| RIP & Printer Media Settings | Optimal printer settings will vary from printer manufacturers. A suggested starting point is setting the pre and post heaters to 122° F (50° C). For the best and most consistent results, a profile should be created using an external color calibrator in conjunction with your RIP and color matching software. If a custom profile is not available, the on-board media setting, Cast Vinyls, typically used for vehicle wraps, is a good place to start. |
| Light Fastness               | The fading time of inkjet ink is a direct result of the inks that you choose to use and the environment where the print is displayed. Contact the ink manufacturer for light-fastness data.  |
| L*                           | 94.33  |
| A*                           | -0.18  |
| B*                           | -0.62  |
| Fire Rating                  | Class A  |
| Core Size                    | 3" ID core   |
| Optimal Service Environment  | For printing: 60°-80° F, 50% Relative Humidity. For end use: -40°-176° F (-40°-80° C).   |
| Ideal Storage Conditions     | 70° F (21° C), 50% R.H. (a controlled environment is recommended); store vertically in original packaging.   |
| Color                        | Bright white PVC   |
| Ink Compatibility            | Compatible with all low-solvent, solvent, UV-curable and latex printers.   |
| Shelf Life                   | 1 year storage in original package under recommended storage conditions above.   |

| SKU        | Size           | UPC Code     | Region |
|------------|----------------|--------------|--------|
| TABNW54150 | 54 in x 150 ft | 848412024708 | AMS    |
| TABNW54300 | 54 in x 300 ft | 848412024715 | AMS    |

Product Performance & Suitability: All of the descriptive information and recommendations should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind. All purchasers shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in agreement signed by officers of seller and manufacturer.